

Cancel Claim 1 and combine it with Claim 10.

CLAIMS

1 1. (Cancelled)

1 2. (Cancelled

1 3. (Previously Presented) A humidity control system comprising:
2 an inside room humidity sensor;
3 a humidity controller coupled to said inside humidity sensor, said
4 humidity controller having a selectively actuatable humidity level selection
5 control for providing a control signal for selecting a target in-room humidity;
6 an outside temperature sensor circuit; and
7 an outside temperature humidity compensator circuit responsively
8 coupled to said outside temperature sensor circuit and to said humidity
9 controller for selectively altering said control signal, wherein said outside
10 temperature humidity compensator circuit includes a compensation network
11 including said outside temperature sensing circuit, and an adjustment control
12 circuit, a control switch having a first switch position to select coupling said
13 inside room humidity sensor directly to said humidity controller and having
14 a second switch position to couple said compensation network and
15 adjustment control circuit to said inside room humidity sensor and to said
16 humidity controller;
17 whereby sensed outside temperature causes said outside temperature
18 humidity compensator circuit to automatically adjust the target in-room
19 humidity produced by said humidity controller.

1 4. (Cancelled)

1 5. (Original) A system as in Claim 3 wherein said compensation
2 network includes:

3 an input divider circuit including said outside sensor circuit; and

4 a first compensating circuit coupled to said inside room humidity
5 sensor and to said input divider circuit to provide a first variable bias signal
6 level responsive to outside temperature sensed by said outside temperature
7 sensor circuit.

1 6. (Original) A system as in Claim 5, wherein said adjustment control
2 circuit includes

3 an output circuit coupled intermediate said inside room humidity
4 sensor and said humidity controller, said output circuit also coupled to said
5 first compensating circuit, said output circuit to provide an output signal to
6 said humidity controller; and

7 a selectively variable circuit coupled to said inside room humidity
8 sensor, to said outside temperature sensor, and to said output circuit to
9 provide a second variable bias signal level,

10 whereby said output circuit provides said output signal determined by
11 said outside temperature sensed and the setting of said selectively variable
12 circuit.

1 7. (Original) A system as in Claim 5, wherein said outside temperature
2 sensor circuit includes

3 a thermistor whose resistive value varies with changes in ambient
4 temperature.

1 8. (Previously Presented) A system as in Claim 6, wherein said
2 selectively variable circuit includes a first manually adjustable
3 potentiometer.

1 9. (Previously Presented) A system as in Claim 8, wherein said input
2 divider circuit includes a second manually adjustable potentiometer to
3 provide controlled calibration of said output signal.

1 10. (Currently Amended) A humidity control system comprising:
2 an inside room humidity sensor;
3 a humidity controller coupled to said inside humidity sensor, said
4 humidity controller having a selectively actuatable humidity level selection
5 control for providing a control signal for selecting a target in-room humidity;
6 an outside temperature sensor circuit; and
7 an outside temperature humidity compensator circuit responsively
8 coupled to said outside temperature sensor circuit and to said humidity
9 controller for selectively altering said control signal.

10 ~~A system as in Claim 1,~~ wherein said outside humidity temperature
11 compensator circuit comprises:

12 a circuit common connection;

13 a power input terminal for coupling to a source of power;

14 a temperature sensitive resistor having a first connection and a second
15 connection coupled to said circuit common connection;

16 a first transistor having a first element coupled to said inside humidity
17 sensor, a second element coupled to said humidity controller, and a third
18 element;

19 a load resistor coupled between said second element and said circuit
20 common connection;

21 a first variable resistor having a wiper element coupled to said third
22 element;

23 a first resistor coupled intermediate said inside room humidity sensor
24 and said first variable resistor;

25 a first diode having a first diode terminal and a second terminal, said
26 first diode terminal coupled to said first variable resistor;

27 a second resistor coupled intermediate said second diode terminal and
28 said first connection;

29 a second transistor having a fourth element coupled to said third
30 element, a fifth element, and a sixth element;

31 a third resistor coupled intermediate said fifth element and said inside
32 room humidity sensor;

33 a fourth resistor coupled intermediate said power input terminal and
34 said sixth element; and

35 a fifth resistor coupled intermediate said sixth element and said circuit
36 common connection,

37 whereby sensed outside temperature causes said outside
38 temperature humidity compensator circuit to automatically adjust
39 the target in-room humidity produced by said humidity controller.

1 11. (Original) A system as in Claim 10, and further including

2 a second diode coupled intermediate said second element and said
3 third element.

12. (Cancelled)

1 13. (Previously Presented) A humidity adjusting method comprising:
2 providing selectively reduced signals indicative of sensed indoor
3 humidity levels;
4 sensing changes in outside temperature and developing temperature
5 controlled adjusting signals indicative of such changes;
6 combining the selectively reduced signals and the adjusting signals for
7 providing output signals for use in controlling the operation of a humidity
8 controller;
9 developing a source of setpoint settings and rate of humidity change
10 settings for a predetermined range of outside temperatures and a
11 predetermined range of percentage of humidity changes associated with
12 changes in outside temperature; and
13 selecting the setpoint setting and the rate of humidity change setting
14 from the source of settings for a desired outside temperature range and a
15 desired rate of humidity change.

1 14. (Previously Presented) For use in humidity control system having a
2 selectively actuatable humidity level selection control for providing a control
3 signal for selecting a target in-room humidity, an outside temperature
4 humidity compensating system comprising:
5 receiving means for receiving indicators of changes in outside
6 temperature;
7 humidity receiving means for receiving humidity signals indicative of
8 the in-room humidity;
9 reducing means for reducing received humidity signals by a selectable
10 predetermined amount and for providing reduced humidity signals;

11 adjusting means for providing adjusting signals for adjusting the
12 control signal in response to received indications of changes in outside
13 temperature; and
14 outputting means for providing output signals in response to the
15 adjusting signals and the reduced humidity signals,
16 whereby the output signals can be utilized to control a humidity
17 controller.

1 15. (Original) A system as in Claim 14, wherein said reducing means
2 includes:
3 rating means for permitting manual selectable settings for defining the
4 rate of percentage of humidity change for a range of temperature changes.

1 16. (Original) A system as in Claim 14, wherein said adjusting means
2 includes:
3 voltage dividing means for shifting voltage levels in response to
4 sensed changes in the outside temperature; and
5 voltage adjusting means for providing the adjusting signals in
6 response to changes in the voltage dividing means.

1 17. (Original) An outside temperature humidity compensation circuit
2 comprising:
3 a first input circuit for receiving humidity signals from a humidity
4 sensor;
5 a second input circuit for coupling to an outside temperature sensor
6 circuit;

7 a first compensating circuit coupled to said first input circuit and said
8 second input circuit to provide a first variable temperature compensating
9 signals in response to changes in outside temperature;

10 an output circuit; and

11 a selectively variable circuit coupled to said first input circuit, to said
12 second input circuit, to said first compensating circuit, and to said output
13 circuit to provide second variable signals to said output circuit,

14 whereby said output circuit provides said second variable signals
15 determined by changes in outside temperature and the setting of said
16 selectively variable circuit.

1 18. (Original) The circuit of Claim 17, and further including a thermistor
2 coupled to said second input circuit.

1 19. (Original) A circuit as in Claim 17, wherein said selectively variable
2 circuit includes a manually adjustable potentiometer for adjusting the
3 effective rate of percentage of humidity change.

1
2 20. (Previously Presented) The Circuit of Claim 17, and further including
3 a control switch coupled between said input circuit and said output circuit,
4 whereby the compensation circuit can be switched active and inactive.
5